



Intel offers multiple categories of RAID products to protect data, increase performance, scale storage, and enhance server availability. A brief description of each category is listed below with details in the pages that follow.

CONTROLLER CARDS AND MODULES

- Best: Intel® Integrated Server RAID signifies unique system boards that are designed to add value above that of a standard RAID add-in card to Intel® Server Boards and Systems.
- Better: Intel® RAID Controllers are add-in cards designed to enable a wide variety of RAID solutions.
- Good: Intel® Embedded Server RAID Technology Software RAID Activation Keys are designed for entry-level RAID solutions.

RAID CACHE BACKUP

- Intel also offers both Battery Backup Units (BBU) and Maintenance-Free Backup options for hardware RAID products with embedded cache. The backup options are listed in the "Backup Option" row of the product tables.

EXPANDER BOARDS

- Intel® RAID Expander Cards are intended for any system with more than 8 drives. As an example of use, 8 RAID ports can be expanded to 24 ports.

PREMIUM FEATURE KEYS

- Intel offers several upgrade features which allow for unique performance enhancements or enhanced data protection.

INTEL® INTEGRATED RAID PRODUCTS



Controller	Intel® Integrated RAID Module RMS25CB080 / 040	Intel® Integrated RAID Module RMT3CB080	Intel® Integrated RAID Module RMS25JB080 / 040	Intel® Integrated RAID Module RMS25PB080 / 040
Market Segment	Mainstream	Mainstream	Entry / Limited Feature	Mainstream
Order Code	RMS25CB080 / RMS25CB040	RMT3CB080	RMS25JB080 / RMS25JB040	RMS25PB080 / RMS25PB040
Processor / RAID On Chip	LSI* 2208	LSI* 2208	LSI* 2308	LSI* 2208
Memory	Embedded 1 GB ECC DDR2 SDRAM	Embedded 512 MB ECC DDR2 SDRAM	2 MB context memory for entry-level hardware RAID calculations	Embedded 1 GB ECC DDR2 SDRAM
PCI Bus Channels	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8
Form Factor	1U capable system board	1U capable system board	1U capable system board	Low-profile PCI Express add-in card
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, and 1E	0, 1, 5, 6, 10, 50, and 60
Backup Options	AXXRSBBU9 (battery backup) AXXRMFBU2 (flash and supercap)	AXXRSBBU9 (battery backup) AXXRMFBU2 (flash and supercap)	N/A	AXXRSBBU9 (battery backup) AXXRMFBU2 (flash and supercap)
Cables	Purchased separately	Purchased separately	Purchased separately	Purchased separately
Intel® Server Board Support	Intel® Xeon® E5 series server boards with a storage I/O module connector	Intel® Xeon® E5 series server boards with a storage I/O module connector	Intel® Xeon® E5 series server boards with a storage I/O module connector	Intel® Xeon® E5 series server boards
Availability	February	February	February	February



NEW



NEW



Controller	Intel® Integrated RAID Module RMT3PB080	Intel® Integrated RAID Module RMS25KB080 / 040	Intel® Integrated RAID Module RMS2MH080	Intel® Integrated RAID Module RMS2AF080 / 040
	6.0 Gb/s SATA 3.0 full hardware RAID Module with standard PCI Express* connector	6.0 Gb/s SAS 2.1 entry-level RAID Module with standard PCI Express* connector	6.0 Gb/s SAS 2.0 RAID Module for use with Intel® Server Boards S552OUR and S5500WB	6.0 Gb/s SAS 2.0 entry-level RAID Module for use with Intel® Xeon® E3 and 5600 series server boards with an I/O module slot
Market Segment	Mainstream	Entry / Limited Feature	Mainstream	Entry
Order Code	RMT3PB080	RMS25KB080 / RMS25KB040	AXXRMS2MH080	AXXRMS2AF080 / AXXRMS2AF040
Processor / RAID On Chip	LSI* 2208	LSI* 2308	LSI* 2108	LSI* 2008
Memory	Embedded 512 MB ECC DDR2 SDRAM	2 MB context memory for entry-level hardware RAID calculations	Embedded 512 MB ECC DDR2 SDRAM	2 MB (on card) for RAID 0, 1, 1E, and 128 MB (from server board) for RAID 5 calculations
PCI Bus	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x4
Channels	8 SATA ports supporting point-to-point 6.0 Gb/s data-transfer rates	8 / 4 SAS / SATA ports supporting point-to-point 6.0 Gb/s data-transfer rates	8 SAS / SATA ports supporting point-to-point 6.0 Gb/s data-transfer rates	8 / 4 SAS / SATA ports supporting point-to-point 6.0 Gb/s data-transfer rates
Form Factor	Low-profile PCI Express add-in card	Low-profile PCI Express add-in card	1U capable system board	1U capable system board
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, and 1E	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 10, and 50
Backup Options	AXXRSBBU9 (battery backup) AXXRMFBU2 (flash and supercap)	N/A	AXXRSBBU7 AXXRSBBU8 (new longer life)	No
Cables	Purchased separately	Purchased separately	Included	Included
Intel® Server Board Support	Intel® Xeon® E5 series server boards	Intel® Xeon® E5 series server boards	Intel® Server Boards S552OUR and S5500WB	Intel® Server Boards S552OUR, S5500WB, S5520HC, S5520SC, S3420GP, and S1200BT
Availability	February	February	Now	Now



Controller	Intel® Integrated RAID Module RMS2LL080 / 040	Intel® Integrated RAID 1U / 2U Midplane	Intel® Integrated RAID Module SROMBSASMR	Intel® Integrated RAID Module AXX4SASMOD
	6.0 Gb/s SAS 2.0 entry-level RAID Module for use with Intel® Xeon® E3 and 5600 series server boards with an I/O module slot	SAS and SATA RAID Module for Intel® Server Systems SR1625UR, SR2600UR, and SR2625UR	Four-port internal RAID Module for 1U, 2U, and pedestal use with Intel® Server Boards S5520HC and S5500WB	Flexible Module offering pass-through SAS and multiple entry-level RAID options
Market Segment	Entry / Limited Feature	Mainstream	Mainstream	Entry
Order Code	AXXRMS2LL080 / AXXRMS2LL040	Midplane included with systems requires AXXRAKSAS2 for hardware RAID activation	AXXROMBSASMR	AXX4SASMOD requires AXXRAKSW5 for RAID 5
Processor / RAID On Chip	LSI* 2008	LSI* 1078	LSI* 1078	LSI* 1064
Memory	2 MB for entry-level hardware RAID calculations	Supports up to 1 GB mini-DIMM ECC DDR2 667 MHz DDR2 SDRAM	Embedded 128 MB ECC DDR2 SDRAM	2 MB for entry-level hardware RAID calculations
PCI Bus	PCI Express* 2.0 x4	PCI Express* x4	PCI Express* x8	PCI Express* x4
Channels	8 / 4 SAS / SATA ports supporting point-to-point 6.0 Gb/s data-transfer rates	8 SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	4 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	4 SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates
Form Factor	1U capable system board	System midplane	1U capable system board	1U capable system board
RAID Levels	0, 1, and 1E	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 1E, and optional RAID 5
Backup Options	No	AXXRSBBU3	AXXRSBBU3	No
Cables	Included	Included	Included	Included
Intel® Server Board Support	Intel® Server Boards S5520UR, S5500WB, S5520HC, S5520SC, S3420GP, and S1200BT	Intel® Server Board S5520UR	Intel® Server Boards S5520UR, S5500WB, S5520HC, S5520SC, S3420GP, and S1200BT	Intel® Server Boards S5520UR, S5500WB, S5520HC, S5520SC, S3420GP, and S1200BT
Availability	Now	Now	Now	Now

SAS 2.0 INTEL® RAID CONTROLLER ADD-IN CARDS



Controller	Intel® RAID Controller RS2SG244	Intel® RAID Controller RS2WG160	Intel® RAID Controller RS25NB008	Intel® RAID Controller RS25SB008
	Scalable performance 6.0 Gb/s SAS RAID Controller with 24 internal and four external ports for SAS / SATA drives	Scalable performance 6.0 Gb/s SAS RAID Controller with 16 internal ports for SAS / SATA drives	Scalable performance dual-core 6.0 Gb/s SAS RAID Controller with 8 external ports for SAS / SATA drives	Scalable performance dual-core 6.0 Gb/s SAS RAID Controller with 8 external ports for SAS / SATA drives and maintenance-free backup unit (Flash-based)
Order Code	RS2SG244	RS2WG160	RS25NB008	RS25SB008
Processor / RAID On Chip	LSI* SAS2108	LSI* SAS2108	LSI* SAS2208	LSI* SAS2208
Memory	512 MB embedded DDR2 ECC memory	512 MB embedded DDR2 ECC memory	1 GB embedded DDR3 ECC memory	1 GB embedded DDR2 ECC memory
PCI Bus	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8
Channels	24 internal and 4 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	16 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates
Form Factor	Full-height, 6.6" length	Full-height, 6.6" length	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60
Intel® Smart Backup Option	AXXRSBBU7 AXXRSBBU8 (new longer life)	AXXRSBBU7 AXXRSBBU8 (new longer life)	AXXRSBBU9	Maintenance-free backup unit (Flash-based) included with add-in card
Cables	Included	Included	Not included	Not included
Availability	Now	Now	August	Now



Controller	Intel® RAID Controller RS2MB044	Intel® RAID Controller RS25DB080	Intel® RAID Controller RS2VB080 / 040
	Scalable performance 6.0 Gb/s SAS RAID Controller with 4 internal and 4 external ports for SAS / SATA drives	Mainstream dual-core 6.0 Gb/s SAS RAID Controller with 8 internal ports for SAS / SATA drives	Mainstream 6.0 Gb/s SAS RAID Controller with 8 internal ports for SAS / SATA drives and maintenance-free backup unit (Flash-based)
Order Code	RS2MB044	RS25DB080	RS2VB080 / RS2VB040
Processor / RAID On Chip	LSI* SAS2108	LSI* SAS2208	LSI* SAS2108
Memory	512 MB embedded DDR2 ECC memory	1 GB embedded DDR3 ECC memory	512 MB embedded DDR2 ECC memory
PCI Bus	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8
Channels	4 internal and 4 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 / 4 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60
Intel® Smart Backup Option	AXXRSBBU7 AXXRSBBU8 (new longer life)	AXXRSBBU9	Maintenance-free backup unit (Flash-based) included with add-in card
Cables	One 8087 to four 7-pin SATA cable included	AXXCBL740MS7P (ordered separately)	Included
Availability	Now	Now	Now

NEW



Controller	Intel® RAID Controller RS25AB080	Intel® RAID Controller RS2BL080 / 040	Intel® RAID Controller RS2PI008
	Mainstream dual-core 6.0 Gb/s SAS RAID Controller with 8 internal ports for SAS / SATA drives and maintenance-free backup unit (Flash-based)	Mainstream 6.0 Gb/s SAS RAID Controller with 8 internal ports for SAS / SATA drives	Mainstream 6.0 Gb/s SAS RAID Controller with 8 external ports for JBODs with SAS / SATA drives
Order Code	RS25AB080	RS2BL080 / RS2BL040 (Standard) RS2BL080DE (with Drive Encryption Management)	RS2PI008 (Standard) RS2PI008DE (with Drive Encryption Management)
Processor / RAID On Chip	LSI* SAS2208	LSI* SAS2108	LSI* SAS2108
Memory	1 GB embedded DDR2 ECC memory	512 MB embedded DDR2 ECC memory	512 MB embedded DDR2 ECC memory
PCI Bus	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8
Channels	8 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 / 4 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60
Intel® Smart Backup Option	Maintenance-free backup unit (Flash-based) included with add-in card	AXXRSBBU7 AXXRSBBU8 (new longer life)	AXXRSBBU7 AXXRSBBU8 (new longer life)
Cables	Purchased separately	Included	Included
Availability	Now	Now	Now



Controller	Intel® RAID Controller RT3WB080	Intel® RAID Controller RS2WC080 / 040	Intel® RAID Controller RS25GB008
	Mainstream SATA-only RAID Controller with 8 ports and SAS expansion support for up to 16 SATA drives	Entry-level 6.0 Gb/s SAS RAID Controller with 8 internal ports for SAS / SATA drives	Entry-level 6.0 Gb/s SAS RAID Controller with 8 external ports for JBOD with SAS / SATA drives
Order Code	RT3WB080	RS2WC080 / RS2WC040	RS25GB008
Processor / RAID On Chip	LSI* SAS2108	LSI* SAS2008	LSI* SAS2308
Memory	256 MB embedded DDR2 ECC memory	2 MB (on card) for RAID 0, 1, 1E, and 128 MB (from server board) for RAID 5 calculations	2 MB context memory
PCI Bus	PCI Express* 2.0 x8	PCI Express* 2.0 x8	PCI Express* 2.0 x8
Channels	8 internal SATA ports supporting SAS expansion and point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 / 4 internal SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	8 external SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)	Low-profile, 6.6" length (MD2 compliant)
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 10, and 50	JBOD
Intel® Smart Backup Option	AXXRSBBU7 AXXRSBBU8 (new longer life)	No	No
Cables	Included	Included	Not included
Availability	Now	Now	August

SAS 1.0 INTEL® RAID CONTROLLER ADD-IN CARDS



Controller	Intel® RAID Controller SRCASBB8I	Intel® RAID Controller SRCASRB	Intel® RAID Controller SRCASLS4I	Intel® RAID Controller SRCATAWB
	8-port internal SAS / SATA RAID in a low-profile, MD2-compliant form factor for mainstream to performance solutions	8-port internal SAS / SATA RAID for mainstream solutions	4-port internal SAS / SATA RAID in a low-profile, MD2-compliant form factor for entry-level to mainstream solutions	8-port SATA RAID supporting up to 16 HDD through an expander backplane for entry-level to mainstream solutions
Order Code	SRCSASBB8I	SRCSASRB	SRCSASLS4I	SRCSATAWB
Processor / RAID On Chip	LSI* 1078	LSI* 1078	LSI* 1078	LSI* 1078
Memory	Embedded 256 MB ECC DDR2 SDRAM	Embedded 256 MB ECC DDR2 SDRAM	Embedded 128 MB ECC DDR2 SDRAM	Embedded 128 MB ECC DDR2 SDRAM
PCI Bus	PCI Express* x8	PCI Express* x4	PCI Express* x8	PCI Express* x4
Channels	8 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	8 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	4 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	8 internal SATA ports with 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length	Low-profile, 7.75" length	Low-profile, 6.6" length	Low-profile, 7.75" length
RAID Levels	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60	0, 1, 5, 6, 10, 50, and 60
Intel® Smart Backup Option	AXXRSBBU6	AXXRSBBU4	AXXRSBBU6	AXXRSBBU4
Cables	Included	Included	Included	Included
Availability	Now	Now	Now	Now



Controller	Intel® RAID Controller SASMF81	Intel® RAID Controller SASUC81	Intel® RAID Controller SASWT41
	8-port SAS / SATA card with host-based RAID capability for entry-level RAID solutions	8-port SAS / SATA with pass through SAS and entry-level hardware RAID 0, 1, 1E, and 10E capability	4-port SAS / SATA with pass through SAS and entry-level hardware RAID 0, 1, 1E, and 10E capability
Order Code	SASMF81	SASUC81	SASWT41
Processor / RAID On Chip	LSI* 1068	LSI* 1068	LSI* 1064
Memory	N/A	2 MB for entry-level hardware RAID calculations	2 MB for entry-level hardware RAID calculations
PCI Bus	PCI Express* x4	PCI Express* x4	PCI Express* x4
Channels	8 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	8 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates	4 internal SAS / SATA ports supporting point-to-point 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length	Low-profile, 6.6" length	Low-profile, 6.6" length
RAID Levels	0, 1, 5, and 10	0, 1, and 1E/10E	0, 1, and 1E/10E
Intel® Smart Backup Option	No	No	No
Cables	Included	N/A	Included
Availability	Now	Now	Now

INTEL® SOFTWARE RAID ACTIVATION KEYS

Most Intel® Xeon® 5500 and 5600 series server boards include Intel® Embedded Server RAID Technology 2 which provides RAID 0, 1, and 10. Software RAID 5 can be enabled on these server boards by adding the AXXRAKSW5 activation key.

Most Intel® Xeon E5 series server boards include 8 SCU storage ports with activation and features corresponding to the following table.


ACTIVATION KEY	PRODUCT NAME	SCU STORAGE FUNCTIONALITY
None	N/A	4-port SATA key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, and 10, and Intel® Rapid Storage Technology Enterprise RAID 0, 1, 5, and 10 (no key)
RKSATA4R5	Intel® RAID C600 Upgrade Key RKSATA4R5	4-port SATA key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, 5, and 10, and Intel® Rapid Storage Technology Enterprise RAID 0, 1, 5, and 10 (BLACK)
RKSATA8	Intel® RAID C600 Upgrade Key RKSATA8	8-port SATA key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, and 10, and Intel® Rapid Storage Technology Enterprise RAID 0, 1, 5, and 10 (BLUE)
RKSATA8R5	Intel® RAID C600 Upgrade Key RKSATA8R5	8-port SATA key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, 5, and 10, and Intel® Rapid Storage Technology Enterprise RAID 0, 1, 5, and 10 (WHITE)
RKSAS4	Intel® RAID C600 Upgrade Key RKSAS4	4-port SAS key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, and 10, and Intel® Rapid Storage Technology Enterprise RAID 0, 1, and 10 (GREEN)
RKSAS4R5	Intel® RAID C600 Upgrade Key RKSAS4R5	4-port SAS key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, 5, and 10 and Intel® Rapid Storage Technology Enterprise RAID 0, 1, and 10 (YELLOW)
RKSAS8	Intel® RAID C600 Upgrade Key RKSAS8	8-port SAS key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, and 10 and Intel® Rapid Storage Technology Enterprise RAID 0, 1, and 10 (ORANGE)
RKSAS8R5	Intel® RAID C600 Upgrade Key RKSAS8R5	8-port SAS key with Intel® Embedded Server RAID Technology 2, RAID 0, 1, 5, and 10 and Intel® Rapid Storage Technology Enterprise RAID 0, 1, and 10 (PURPLE)

INTEL® RAID EXPANDER BOARDS (SAS EXPANDERS)

NEW



NEW



Expander Board	Intel® RAID Expander RES2SV240	Intel® RAID Expander RES2CV360 / 240
Description	24-port, 6.0 Gb/s-capable expander card for use with Intel® RAID products	36 / 24-port, 6.0 Gb/s-capable expander card for use with Intel® RAID products
Order Code	RES2SV240 (with 6 cables) RES2SV240NC (no cables)	RES2CV360 (no cables) / RES2CV240 (no cables)
Processor / RAID On Chip	LSI* 6.0 Gb/s Expander	LSI* 6.0 Gb/s Expander
Channels	24 SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates	36 / 24 SAS / SATA ports supporting point-to-point 6.0 Gb/s and 3.0 Gb/s data-transfer rates
Form Factor	Low-profile, 6.6" length (MD2 compliant) can be mounted in PCI Express* slot or chassis wall	Unique system board that requires chassis mounting point
Power Options	Standard PCI Express* x4 connector or RA 4-pin power connector	RA 4-pin power connector
Management	SGPIO	SGPIO
Fault LED Headers	Includes 2 pin headers to support each SAS port	Includes 2 pin headers to support each SAS port
Availability	Now	February

INTEL® RAID PREMIUM FEATURES

These features are available as an upgrade for all LSI* SAS2108 processor-based Intel® RAID products. To identify products with this processor, please refer to the Processor row of the preceding feature tables. The Premium Feature Keys are described below.

PREMIUM FEATURE	SSD CACHE WITH FAST-PATH I/O	DRIVE ENCRYPTION MANAGEMENT	RAPID RECOVERY SNAPSHOT
Key Benefits	<ul style="list-style-type: none"> SSD Cache allows Solid-State Drives to be utilized as additional cache for the RAID Controller. The cache can be used for both reads and writes to assist storage performance. Fast-Path I/O accelerates communication with SSDs providing up to 150,000 I/O reads per second for small, random block-size I/O activity. This is a dramatic increase over solutions not using Fast-Path. 	<ul style="list-style-type: none"> Drive encryption management enables authentication key management, auto-lock, and instant erase of self-encrypting drives (SED). All drives eventually leave the data center and the use of SEDs helps reduce risk of data breaches. Instant erase significantly reduces the cost and time of repurposing or retiring drives. 	<ul style="list-style-type: none"> Rapid Recovery Snapshot allows users to capture source volume data changes and either restore files or rollback applications to a previous Point in Time (PiT). Rapid recovery of lost data from disk can occur within minutes, minimizing the downtime experienced by users and eliminating the lengthy process of restoring data from tape. By isolating a server's boot volume to a separate virtual drive and enabling the auto snapshot feature, users can be guaranteed that bootable snapshots exist, should operating system corruption occur.
Order Code	AXXRPFKSSD	AXXRPFKDE	AXXRPFKSNSH
Availability	Now	Now	Now

These features are available as an upgrade for all LSI* SAS2208 processor-based Intel® RAID products. To identify products with this processor, please refer to the Processor row of the preceding feature tables. The Premium Feature Keys are described below.

PREMIUM FEATURE	SSD CACHE WITH FAST-PATH I/O	DRIVE ENCRYPTION MANAGEMENT	RAPID RECOVERY SNAPSHOT
Key Benefits	<ul style="list-style-type: none"> SSD Cache allows Solid-State Drives to be utilized as additional cache for the RAID Controller. Frequently accessed information is stored in the cache, allowing rapid access. Fast-Path I/O accelerates communication with SSDs providing up to 465,000 I/O reads per second for small, random block-size I/O activity. This is a dramatic increase over solutions not using Fast-Path. 	<ul style="list-style-type: none"> Drive encryption management enables authentication key management, auto-lock, and instant erase of self-encrypting drives (SED). All drives eventually leave the data center and the use of SEDs helps reduce risk of data breaches. Instant erase significantly reduces the cost and time of repurposing or retiring drives. 	<ul style="list-style-type: none"> Rapid Recovery Snapshot allows users to capture source volume data changes and either restore files or rollback applications to a previous Point in Time (PiT). Rapid recovery of lost data from disk can occur within minutes, minimizing the downtime experienced by users and eliminating the lengthy process of restoring data from tape. By isolating a server's boot volume to a separate virtual drive and enabling the auto snapshot feature, users can be guaranteed that bootable snapshots exist, should operating system corruption occur.
Order Code	AXXRPFKSSD2	AXXRPFKDE2	AXXRPFKSNSH2
Availability	Now	Now	Now

For more information, visit www.intel.com/go/RAID

All products and dates specified are preliminary based on current expectations and are subject to change without notice. Availability in different channels may vary. Intel and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2012 Intel Corporation. All rights reserved. 0112/JD/MS 252627-036US January 2012